

Max. Flow Rate: 285 GPH (1,080 LPH)

- Separ 2000 series water separators fuel filters are a simple solution to many different fuel related problems.
- Five separate stages of filtration ensure 99.9% water separation (Certified TUV Report using SAE J1839) at maximum flow.
- Low restriction reduces wear on fuel pumps and ensures full RPMs.
- Backflushable (cleanable) element reduces down time and costly element changes.
- Marine version with U.S. Coast Guard-accepted metal heat deflector.

INDUSTRIAL



MARINE



Shown: Industrial (left to right) 2000/18, 2000/18U
Marine (left to right) 2000/18D-G, 2000/18UD-G

Inlet / Outlet Connections

Single Unit: 1 1/16-12 Straight o-ring SAE
Duplex Unit: Shipped with #12 Male JIC Flare
(other adapters available)
Inlet and Outlet Pipe connection 22mm.

Ordering Specifications

	SWK-2000/18	U	M	MK	K	KD	D	A	- G
Duplex	_____	_____	_____	_____	_____	_____	_____	_____	_____
Metal bowl	_____	_____	_____	_____	_____	_____	_____	_____	_____
Metal bowl w/ contacts	_____	_____	_____	_____	_____	_____	_____	_____	_____
Clear bowl w/ water contacts	_____	_____	_____	_____	_____	_____	_____	_____	_____
Clear bowl w/ metal heat deflector and water contacts	_____	_____	_____	_____	_____	_____	_____	_____	_____
Clear bowl w/ metal heat deflector	_____	_____	_____	_____	_____	_____	_____	_____	_____
Automatic switchable duplex	_____	_____	_____	_____	_____	_____	_____	_____	_____
Gauge	_____	_____	_____	_____	_____	_____	_____	_____	_____

We reserve the right to alter the specification without prior notice.

Pressure Drop



